



ALUSLEVYT



DIN 125

Ruuville M	sisä Ø d1 mm	ulko Ø d2 mm	s mm	Pinnoit- tamaton	Messinki	Hapon- kestävä A4
3	3,2	7	0,5			0412 3
4	4,3	9	0,8		0400 4	0412 4
5	5,3	10	1,0		0400 5	0412 5
6	6,4	12	1,6		0400 6	0412 6
8	8,4	16	1,6		0400 8	0412 8
10	10,5	20	2,0		0400 10	0412 10
12	13	24	2,5	0405 12	0400 12	0412 12
16	17	30	3,0	040516		0412 16
18	19	34	3,0			0412 18
20	21	37	3,0	0405 20		0412 20
24	25	44	4	0405 26		0412 24
27	28	50	4	0405 28		0412 27
30	31	56	4	0405 30		0412 30
33	34	60	5	0405 34		
39	40	72	6	0405 40		



ISO 7089

Ruuville M	sisä Ø d1 mm	ulko Ø d2 mm	s mm	Sinkitty HV 200 8.8 liitokset	Sinkitty HV 300 10.9 liitokset
2	2,2	5	0,3	5149 2	
2,5	2,7	6	0,5		
3	3,2	7	0,5	5149 3	
4	4,3	9	0,8	5149 4	
5	5,3	10	1,0	5149 5	
6	6,4	12	1,6	5149 6	
7	7,4	14	1,6		
8	8,4	16	1,6	5149 8	
10	10,5	20	2,0	5149 10	5149 981 0
12	13	24	2,5	5149 12	5149 981 2
14	15	28	2,5	5149 14	5149 981 4
16	17	30	3,0	5149 16	5149 981 6
18	19	34	3,0	5149 18	
20	21	37	3,0	5149 20	5149 982 0
22	23	39	3	5149 22	
24	25	44	4	5149 24	5149 982 4
27	28	50	4	5149 27	5149 982 7
30	31	56	4	5149 30	5149 983 0
33	34	60	5	5149 33	5149 983 3
36	37	66	5	5149 36	5149 983 6
39	40	72	6	5149 39	
42	43	78	7	5149 42	
48	50	92	8	5149 48	
60	62	110	9	5149 60	
64	66	115	9	5149 66	

ISO 7090



Ruuvi M	sisä Ø d1 mm	ulko Ø d2 mm	s mm	Kuuma sinkitty HV200
8	9,0	16,3	1,9	0407 009 208
10	10,5	20,0	2,5	0407 009 210
12	13,5	23,5	3,0	0407 009 212
16	17,2	29,5	3,0	0407 009 216
18	19,3	33,4	3	0407 009 218
20	21	37	3	0407 009 220
24	26	44	4	0407 009 224
27	30	50	4	0407 009 227
30	33	56	4	0407 009 230
36	39	66	5	0407 009 236
39	42	70,8	6	0407 009 239
42	45	76,8	8	0407 009 242
Ruuvi M	sisä Ø d1 mm	ulko Ø d2 mm	s mm	Pinnoittama- ton teräs
56	62	105	10	4642 806 56
Ruuvi M	sisä Ø d1 mm	ulko Ø d2 mm	s mm	Sinkitty
52	56	98	8	5149 975 2

DIN 1440



Ruuville M	sisä Ø d1 mm	ulko Ø d2 mm	s mm	Sinkitty
16	16	28	3	0496 16