

GYPROC GN 13 NORMAL



PRODUCT DESCRIPTION

Gyproc GN 13 Normaali is a durable, easy-to-work-with standard plasterboard developed specifically for interior ceiling cladding. The board features a gypsum core faced with paperboard on both sides. It has a smooth, even surface and tapered edges that create a recess for joint tape. The weight is approximately 8.4 kg/m². Gyproc Habito or Gyproc GEK 13 boards are recommended for interior wall cladding.

APPLICATION

The product is primarily recommended for use in: repairing ceiling and wall surfaces; ceiling surfaces in fire-rated structures; interior walls and the interior surfaces of exterior walls; and interior walls and the interior surfaces of exterior walls in fire-rated structures. Secondary applications include: curved walls and ceilings, and fire protection for steel structures.

HANDLING

The use of gloves is recommended when cutting the sheet.

TECHNICAL INFORMATION

Weight (per square meter)	8.4 kg/m ²
Thickness	12.5 mm
Width	1200.0 mm
Material	Plasterboard
Edge profile (long side)	Tapered edge O
Edge profile (short side)	Straight edge N
Flexural strength (lateral)	2.4 MPa
Flexural strength (longitudinal)	6.2 MPa
Modulus of elasticity (lateral)	1.6 GPa
Modulus of elasticity (longitudinal)	2.1 GPa
Tolerance (Thickness)	±0,3
Tolerance (Length)	+0/-4
Tolerance (Width)	+0/-3
Tolerance (Weight)	±0,4
Fireclass	A2-s1, d0
Thermal resistance	0.06 m ² °C/W
Water vapour resistance	3,0-4,5 x 10 ⁻³ m/s·Pa
Product approvals	CE, M1, EPD, suitable for Nordic Swan Ecolabelled construction