

1. Unique identification code of the product type: Dry-pressed ceramic tiles with low water absorption  $0,5 < E \leq 3 \%$   
Group BI b, normative (Annex) H, glazed (GL)
2. Intended use:  
Ceramic tiles, dry-pressed for internal and external use
3. Name and contact information of manufacturer  
Hitit Seramik San. Tic. A.Ş.  
Organize Sanayi Bölgesi  
PK:43 64100  
UŞAK  
TURKEY
4. System of assessment and verification of constancy of performance AVCP 4.
5. Harmonized Standard: EN 14411:2016
6. Declared Performance

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	A1FL	EN 14411:2016
Release of dangerous substances for: -Cadmium -Lead	EN ISO 10545-15 NPD NPD	
Breaking strength Modulus of rupture	thickness $\geq 7,5$ mm 1100N thickness $< 7,5$ mm 700N $\geq 30$ N/mm <sup>2</sup> EN ISO 10545-4	
Slipperiness	-	
Durability	EN ISO 10545-12	
Internal use: External use: freeze-thaw resistance	Pass Pass	

The product described in the first item has the performance declared at item 6. The full responsibility for this performance statement only belongs to the manufacturer given in item 3.

Behalf of manufacturer signed: Yusuf YURDUNUSEVER, Factories Manager

07.03.2018

