



#### Clear the air, quickly and efficiently

When you want your kitchen air cleaned quickly, you want the 600 ExtractionTech Hood. Bolstered by a powerful motor that offers two speed options, you'll never struggle to remove unwanted smells or fumes in the kitchen again.

### Product Benefits & Features

#### Keep kitchen air clean with this powerful Hood Motor

This powerful, advanced Hood Motor ensures that your kitchen remains free from unwanted fumes and cooking smells. It clears the air quickly and efficiently.

- Push button controls with 3 speeds
- Air extraction or recirculation possible, charcoal filter included.
- Cooker hood lamps type and number: LED spotlight, 2
- Grease filter type and number: Aluminium Cassette, 3
- Installation type: Chimney, width 90 cm



#### Long life and great lighting – let LEDlights lead the way

Enjoy expert illumination while you cook. Our LEDlights use far less energy than other lights and provide excellent visibility in the kitchen, ensuring you cook with greater confidence and agility.



#### Standard grease filter for a clean kitchen

Our reliable grease filter means you can always enjoy a clear cooking space. When a new filter is required, it can be easily washed or replaced. Your kitchen will be cleaner for longer.

#### Hood control at the push of a button

Enjoy total hood-control at the push of a button. Simply press to increase or decrease the hood's power, so you can experience a clear cooking environment.

Product Specification

Brand	Electrolux	Connection to hob (H2H)	No
Nordic_Width_Cm	90 cm	Lamp type	LED spotlight
Installation	Chimney	Lamp nº of	2
Color	Stainless Steel	Motors nº of	1
External evacuation	Yes	Type of filter	Aluminium Cassette
Recirculatory	Yes	Grease filter nº of	3
Air outlet	150	Charcoal filter	1, Included
Speeds	3	Charcoal filter type	ECFB01
Fluid dynamic efficiency class	D	Charcoal filter PNC	902 979 876
Lighting efficiency class	A	Minimum distance from cooking top ELECTRIC	50
Grease filter efficiency class	C	Minimum distance from cooking top GAS	65
Dimensions HxWxD in mm	678x898x450	No return flap	Yes
Annual Energy consumption, KWh/annum	97.4	Weight net cleaner and accessories no packaging	13.2
Capacity intensive, m³/h	0	Height max. external	1180
Capacity, Max m³/h	600	Cord length external	1.4
Capacity, Min m³/h	295	Voltage	220-240
Recirculation Intensive, m³/h	0	Required fuse (A)	No
Recirculation Max, m³/h	415	Product Number Code	942 022 430
Recirculation Min, m³/h	250	Bar code	7332543674015
Sound power intensive, dB(A)	0	B2B MaterialGroup2	001
Sound power max speed, dB(A)	68	Product Class	Cooker_Hood
Sound power min speed, dB(A)	51		
Recirc. sound power max, dB(A)	73		
Recirc. sound power min, dB(A)	62		

