

DECLARATION OF PERFORMANCE

No. 0204-001-01-2013

1. Unique identification of the product type:

RBS Injection Resin TE

2. Type, batch or serial number or any other elements allowing identification of the construction product as required under Article 11 (4) of the CPR:

019

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Injection of vertical cracks in concrete, brickwork & masonary. Filling voids and joints where little or no movement is anticipated. Injection into single sided cracks where depth and quantity of resin needs to be controlled.

4. Name, registered trade name or registered trademark and contact address of the manufacturer as required under article 11 (5):

Resapol Ltd Unit 8 Aspul Court Moss Industrial Estate Leigh Lancashire WN7 3PT United Kingdom

t: +44 (0) 1942 609001 f: +44 (0) 1942 609006

info@resapol.com

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 4

6. Harmonised standard of product specified:

EN 1504-3:2005

Resapol Ltd performed manufacturers tasks including initial and continued inspection of the manufacturing plant and of factory control. We are solely responsible for continuous surveillance, assessment and evaluation of factory production control.



Resapol Ltd, Unit 8 Aspul Court, Moss Industrial Estate, Leigh, Lancashire. WN7 3PT Tel: +44 (0) 1942 609001 Fax: +44 (0) 1942 609006 Email: <u>info@resapol.com</u> Website: <u>www.resapol.com</u>

Essential Characteristics	Performance	Harmonised Technical Specification
Compressive Strength	Class R4 (≥ 45MPa)	
Chloride Ion Content	≤ 0.05%	
Adhesive Bond Strength	≥ 2.0MPa	EN1504-3:2005
Tensile Strength	> 15MPa	
Flexural Strength	> 30MPa	
Carbonation Resistance	D _k ≤ Control Concrete	
Dangerous Substances	Complies with 5.4	

The information provided in this DOP is given in good faith based on Resapol Limited current knowledge and experience. No warranty in respect of fitness for a purpose, or any other liability whatsoever can be inferred from the information contained within this DOP. Users should determine the suitability of the materials for their particular application and should always refer to the most recent issue of the Product Data Sheet for the product concerned. All materials are supplied in accordance with our standard terms and conditions of sale (available upon request).