

KONE TranSys™ DX visual options


Future-proof your building with this powerful, durable connected elevator solution for moving goods in demanding environments. The KONE TranSys DX combines power with premium-quality design and can be customized with a range of materials.

Key specifications


- API ready
- Connected
- Max. speed 1.6 m/s
- Max. load capacity 5,000 kg
- Max. travel 40 m
- Max. floors 12
- Max. persons 66
- Max. group size 4

Walls

Painted steel



P51
Misty Gray
(RAL 9006)



P62
Blue Reflection

P63
Cottongrass White
(RAL 9003)

Brushed stainless steel



F/ST43
Silver
AISI 441/443

Corrosion resistant steel



A
Acid Proof
(AISI316)



F1
Asturias Satin
(AISI304)


Resistant stainless steel



F2
Asturias Satin
(Anti-fingerprint)



K
Scottish Quad



TS1
Flemish Linen

Local wall

Z
Raw surface for local paint or decorative panels

Smart laminate

L243
Ultimate Gray

Transparent glass

TW1
Glass

Floors

Rubber




RC30
Carbon Black



RC31
Quartz Gray

Available until April 2027



RC36
Silver Grey

Available from December 2026

Metal plate



AL
Aluminium



SS
Stainless steel



ST
Chequered steel

Plywood



FFP
Film Faced Plywood

Local flooring

0
Raw surface for local finishing

Doors

Painted steel



P51
Misty Gray
(RAL 9006)

P63
Cottongrass White
(RAL 9003)

Brushed stainless steel



F/ST43
Silver
AISI 441/443

Corrosion resistant steel



A
Acid Proof
(AISI316)




F1
Asturias Satin
(AISI304)

Resistant stainless steel



F2
Asturias Satin
(Anti-fingerprint)



K
Scottish Quad



TS1
Flemish Linen

Local door

Z
Raw surface for local paint or decorative panels

Transparent glass

TW1
Glass

Note:
- E Extended lead time
- Nordic Swan Ecolabel: Material can be used in Nordic Swan Ecolabelled buildings.
- LEED/BREEAM: Material meets LEED/BREEAM low-emitting materials requirements. Accessories are not in scope of the requirements.

Ceilings*

Direct lighting




CL80
Finish: Cottongrass White (P63)
Silver (F/ST43)



CL96
Finish: Cottongrass White (P63)
Silver (F/ST43)

Indirect lighting



CL109
Finish: Cottongrass White (P63)
Silver (F/ST43)

Integrated ceiling



LF1 / LF1V (EN81-71 Cat.2) **
Finish: Cottongrass White (P63)
Silver (F/ST43)

Firefighter (EN81-72 compliant) and vandal (EN81-71 compliant)



CL80V / CL80FF / CL80FFL
Finish: Cottongrass White (P63)
Silver (F/ST43)



CL96V / CL96FF / CL96FFL
Finish: Cottongrass White (P63)
Silver (F/ST43)

Handrails




HR64 - HR64TR (EN81-70)
Silver (F/ST43)
Painted Carbon Black (P70)
(anti-bacterial treatment)



HR81 – HR81TR (EN81-70)
Silver (F/ST43)
Painted Carbon Black (P70)
(anti-bacterial treatment)



HR94 * (EN81-70 & EN81-71 Cat.2)
Silver (F/ST43)



HR64TR and HR81TR
are continuous
versions

Handrail finishes

- Asturias Satin (F)
- Painted Carbon Black (P70)

Ceiling finishes

- Silver (F/ST43)
- Cottongrass White (P63)

Buffer rails



BR1
TS - Flemish Linen



PR5
Solid wood: Oak/Beech



PR6
Brushed stainless steel

Mirrors



Mirrors are available as partial height, full width with clear glass without fixings

Note:
- E Extended lead time
- Nordic Swan Ecolabel: Material can be used in Nordic Swan Ecolabelled buildings.
- LEED/BREEAM: Material meets LEED/BREEAM low-emitting materials requirements. Accessories are not in scope of the requirements.

* All ceilings available up to 2500 kg

** LF1 and LF1V are the only ceilings for cars over 4000 kg

Car operating panel (COP)

COP



KONE Interact 10



KONE Interact 20

Faceplate finishes

Silver (F/ST43)

Carbon Black (CB)*

Mounting type

COP: flush
Buttons: flush and surface (EN81-72 compliant)

COP Display



5,7” LCD**



Full graphic 7” LCD**



10.1” Smart TFT*

COP lens



Black, round



Black, rectangular



Magic Mirror, round*



Magic Mirror, rectangular*

Note:


- (E) Extended lead time
- Nordic Swan Ecolabel: Material can be used in Nordic Swan Ecolabelled buildings.
- LEED/BREEAM: Material meets LEED/BREEAM low-emitting materials requirements. Accessories are not in scope of the requirements.

* Only for KONE Interact 20

** Only for KONE Interact 10

KSS 140 – Vandal resistant

COP



KSC 143PH (Partial height)
KSC 143FH (Full height)

Faceplate finishes

Silver (F/ST43)

Scottish Quad (K)

Mounting type

COP: flush
Button: surface


Landing devices



KSI 143



KSL 140




KSH 150

KSS H – Accessible excellence



KSC H70, up to 12 buttons
KSC H40, up to 6 buttons

Landing devices (surface mounted)



KSL 710

Faceplate finishes

Asturias Satin (F)



Note:
- (E) Extended lead time
- Nordic Swan Ecolabel: Material can be used in Nordic Swan Ecolabelled buildings.
- LEED/BREEAM: Material meets LEED/BREEAM low-emitting materials requirements. Accessories are not in scope of the requirements.

Landing user interface (surface mounted)

Landing call stations



KSL 186



KSL280



KSL284



KSL286 simplex



KSL286 douplex

Hall displays



KSH280



KSI286

Landing call stations



KLX02

Hall display



KIX01

Faceplate finishes

Silver (ST4)

Carbon Black (CB)

Landing user interface (flush mounted)

Landing call stations



KSL 750



KSK751



KSK750

Faceplate finishes

Silver (ST4)

Carbon Black (CB)

Hall displays



KSI 756



KSH 750



KSI 753



KSA 753

KONE provides innovative and eco-efficient solutions for elevators, escalators, automatic building doors and the systems that integrate them with today's intelligent buildings. We support our customers every step of the way: from design, manufacturing and installation to maintenance and modernization. KONE is a global leader in managing the smooth flow of people and goods throughout buildings. This makes us a reliable partner throughout the building life cycle. We are fast, flexible, and we have a well-deserved reputation as a technology leader, with such innovations as KONE 24/7 Connected Services and KONE UltraRope®. KONE employs over 60,000 dedicated experts to serve you globally and locally.

KONE Corporation

Corporate offices
Keilasatama 3
P.O. Box 7
Espoo, 02150
Finland

Tel.: +358 (0)204 75 1
Fax: +358 (0)204 75 4496

Business Identity Code: 1927400-1

This publication is for general informational purposes only and we reserve the right at any time to alter the product design and specifications. No statement this publication contains shall be construed as a warranty or condition, express or implied, as to any product, its fitness for any particular purpose, merchantability, quality or representation of the terms of any purchase agreement. Minor differences between printed and actual colors may exist. KONE MonoSpace® DX, KONE EcoDisc® and People Flow® are registered trademarks of KONE Corporation. Copyright © 2026 KONE Corporation.

www.kone.com

Dedicated to
People Flow™