

SWISSTEC Sourcing Ltd.

Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,
Thu Dau Mot City, Binh Duong Province. Vietnam.



Document No.: KKM051901-040

Item No: 502016221






Description:

CBS PAN HD TX30 HALF THRD WZP CR3 WAX STL 5um 6x80

Material: Carbon steel

Certificate No.: CPR-J-00480-19

Report No.: 1015-CPR-30-11526/5/JZ

	Nominal diameter	Inner thread diameter	Total length	Head diameter	Thread length	Torsional ratio $F_{tor,k}/R_{tor,k}$	Withdrawal parameter (Loading across / along the fibre) (N/mm^2)	Head pull-through parameter (N/mm^2)	Yield moment (Ring / Smooth section) $I_2 = 1d$ (Nmm)	Tensile capacity (kN)
Description	(mm)	(mm)	(mm)	(mm)	(mm)	(Nm)	(N/mm^2)	(N/mm^2)	(Nmm)	(kN)
										
6x80	5.7 - 6.0	3.6 - 3.85	78.5 - 80.0	11.6 - 12.0	46 - 50	3.2	14.54 / 11.82	26.89	11470 / 16455	12.31
Characteristic density of wood ρ_k (kg/m ³)						450	350	350	-	
Durability (i.e. corrosion protection)						Blue/yellow zinc plated Cr3, 5µm (Service Class 3 acc. To EN 1995-1-1)				

The manufacturer declares for:

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 11 Mar 2019



Hieu Trong Nguyen