

# SWISSTEC Sourcing Ltd.

Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,  
Thu Dau Mot City, Binh Duong Province. Vietnam.



Document No.: KKM051901-048

Item No: 502016229











**Description:**

CBS PAN HD TX20 FULL THRD SST A2 PASSIVATED WAX 4x35

Material: A2

Certificate No.: CPR-J-00482-19

Report No.: 1015-CPR-30-11526/7/JZ

	Nominal diameter	Inner thread diameter	Total length	Head diameter	Thread length	Torsional ratio $F_{tor,k}/R_{tor,k}$	Withdrawal parameter (Loading across / along the fibre) $(N/mm^2)$	Head pull-through parameter $(N/mm^2)$	Yield moment $I_2 = 1d$ $(Nmm)$	Tensile capacity $(kN)$
Description	(mm)	(mm)	(mm)	(mm)	(mm)	(Nm)	(N/mm <sup>2</sup> )	(N/mm <sup>2</sup> )	(Nmm)	(kN)
										
4x35	3.75 - 4.0	2.3 - 2.6	33.75 - 35.0	7.64 - 8.0	Full	1.74	16.34 / 12.67	30.75	1690	3.07
Characteristic density of wood $\rho_k$ (kg/m <sup>3</sup> )						350	350	350	-	
Durability (i.e. corrosion protection)						Stainless steel A2 (Service Class 3 acc. To EN 1995-1-1)				

**The manufacturer declares for:**

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 11 Mar 2019



Hieu Trong Nguyen