

SWISSTEC Sourcing Ltd.

Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,
Thu Dau Mot City, Binh Duong Province. Vietnam.



Document No.: KKM051901-059

Item No: 502016250






Description:

CBS PAN HD TX30 HALF THRD SST A2 PASSIVATED WAX 6x50

Material: A2

Certificate No.: CPR-J-00484-19

Report No.: 1015-CPR-30-11526/9/JZ

	Nominal diameter	Inner thread diameter	Total length	Head diameter	Thread length	Torsional ratio $F_{tor,k}/R_{tor,k}$	Withdrawal parameter (Loading across / along the fibre) (N/mm^2)	Head pull-through parameter (N/mm^2)	Yield moment (Ring / Smooth section) $I_2 = 1d$ (Nmm)	Tensile capacity (kN)
Description	(mm)	(mm)	(mm)	(mm)	(mm)	(Nm)				
										
6x50	5.7 - 6.0	3.6 - 3.85	48.75 - 50.0	11.6 - 12.0	28.75 - 31.25	2.42	14.61 / 12.25	26.71	7537 / 6129	6.45
Characteristic density of wood ρ_k (kg/m ³)						350	350	350	-	
Durability (i.e. corrosion protection)						Stainless steel A2 (Service Class 3 acc. To EN 1995-1-1)				

The manufacturer declares for:

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 11 Mar 2019



Hieu Trong Nguyen