

SWISSTEC Sourcing Ltd.

Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,
Thu Dau Mot City, Binh Duong Province. Vietnam.



Document No.: KKM051901-107






Item No: 502016639

Description:

CBS PAN HD TX15 FULL THRD WZP CR3 WAX STL 5um 3x20

Material: Carbon steel

Report No.: 1015-CPR-30-14146/1/JD

	Nominal diameter	Inner thread diameter	Total length	Head diameter	Thread length	Torsional ratio $F_{tor,k}/R_{tor,k}$	Withdrawal parameter (Loading across / along the fibre) (N/mm^2)	Head pull-through parameter (N/mm^2)	Yield moment $I_2 = 1d$ (Nmm)	Tensile capacity (kN)
Description	(mm)	(mm)	(mm)	(mm)	(mm)	(Nm)	(N/mm^2)	(N/mm^2)	(Nmm)	(kN)
										
3x20	2.8 - 3.0	1.75 - 2.0	18.95 - 20.0	5.7 - 6.0	Full	2.55	17.67 / 12.42	29.53	1555	3.26
Characteristic density of wood ρ_k (kg/m ³)						450	350	350	-	
Durability (i.e. corrosion protection)						Blue/yellow zinc plated Cr3, 5µm (Service Class 3 acc. To EN 1995-1-1)				

The manufacturer declares for:

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 18 Apr 2019



Hieu Trong Nguyen