SWISSTEC Sourcing Ltd.

Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,
Thu Dau Mot City, Binh Duong Province. Vietnam.

CE

Document No.: *KKM051901-137*

Item No: *502016670*

Description:
CBS PAN HD TX30 HALF THRD WZP CR3 WAX STL 5um 6x60

Material: *Carbon steel*

Certificate No.: *CPR-J-00480-19*

Report No.: *1015-CPR-30-11526/5/JZ*

Description	Nominal diameter (mm)	Inner thread diameter (mm)	Total length (mm)	Head diameter (mm)	Thread length (mm)	Torsional ratio $F_{tor,k}/R_{tor,k}$ (Nm)	Withdrawal parameter (Loading across / along the fibre) (N/mm^2)	Head pull-through parameter (N/mm^2)	Yield moment (Ring / Smooth section) l2 = 1d (Nmm)	Tensile capasity (kN)
										
6x60	5.7 - 6.0	3.6 - 3.85	58.5 - 60.0	11.6 - 12.0	34.5 - 37.5	3.2	14.54 / 11.82	26.89	11470 / 16455	12.31
Characteristic density of wood ρ_k (kg/m^3)						450	350	350	-	
Durability (i.e. corrosion protection)						Blue/yellow zinc plated Cr3, 5µm (Service Class 3 acc. To EN 1995-1-1)				

The manufacturer declares for:

The product is in accordance with EN 14592:2008+A1:2012 “Timber Structures – Dowel - Type fasteners – Requirements”.

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 11 Mar 2019

Hieu Trong Nguyen