

SWISSTEC Sourcing Ltd.



Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,
Thu Dau Mot City, Binh Duong Province. Vietnam.



Document No.: KKM051901-159

Item No: 502016692

Description:

CBS PAN HD TX30 HALF THRD SST A2 PASSIVATED WAX 6x60

Material: A2

Certificate No.: CPR-J-00484-19

Report No.: 1015-CPR-30-11526/9/JZ

Description	Nominal diameter (mm)	Inner thread diameter (mm)	Total length (mm)	Head diameter (mm)	Thread length (mm)	Torsional ratio $F_{tor,k}/R_{tor,k}$ (Nm)	Withdrawal parameter (Loading across / along the fibre) (N/mm ²)	Head pull-through parameter (N/mm ²)	Yield moment (Ring / Smooth section) $I_2 = 1d$ (Nmm)	Tensile capacity (kN)
6x60	5.7 - 6.0	3.6 - 3.85	58.5 - 60.0	11.6 - 12.0	34.5 - 37.5	2.42	14.61 / 12.25	26.71	7537 / 6129	6.45
Characteristic density of wood ρ_k (kg/m ³)						350	350	350	-	
Durability (i.e. corrosion protection)						Stainless steel A2 (Service Class 3 acc. To EN 1995-1-1)				

The manufacturer declares for:

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 11 Mar 2019



Hieu Trong Nguyen