

SWISSTEC Sourcing Ltd.



Think Sourcing. Think SWISSTEC

18L1-2 Street 3, Vietnam-Singapore Industrial Park 2,
Thu Dau Mot City, Binh Duong Province. Vietnam.



Document No.: KKM051901-161

Item No: 502016694

Description:

CBS PAN HD TX30 HALF THRD SST A2 PASSIVATED WAX 6x80

Material: A2

Certificate No.: CPR-J-00484-19

Report No.: 1015-CPR-30-11526/9/JZ

| Description | Nominal diameter (mm) | Inner thread diameter (mm) | Total length (mm) | Head diameter (mm) | Thread length (mm) | Torsional ratio $F_{tor,k}/R_{tor,k}$ (Nm) | Withdrawal parameter (Loading across / along the fibre) (N/mm ²) | Head pull-through parameter (N/mm ²) | Yield moment (Ring / Smooth section) $I_2 = 1d$ (Nmm) | Tensile capacity (kN) |
|--|--------------------------|-------------------------------|----------------------|-----------------------|-----------------------|--|--|---|--|--------------------------|
| | | | | | | | | | | |
| 6x80 | 5.7 - 6.0 | 3.6 - 3.85 | 78.5 - 80.0 | 11.6 - 12.0 | 46.0 - 50.0 | 2.42 | 14.61 / 12.25 | 26.71 | 7537 / 6129 | 6.45 |
| Characteristic density of wood ρ_k (kg/m ³) | | | | | | 350 | 350 | 350 | - | |
| Durability (i.e. corrosion protection) | | | | | | Stainless steel A2 (Service Class 3 acc. To EN 1995-1-1) | | | | |

The manufacturer declares for:

The product is in accordance with EN 14592:2008+A1:2012 "Timber Structures – Dowel - Type fasteners – Requirements".

This declaration of conformity is valid until any changes in the product, the raw material or the production process is performed, which would significantly change the declared characteristics.

Date: 11 Mar 2019



Hieu Trong Nguyen