

Product information

AIRFELT AIRFELT TK

Thermo bonded polyester fiber
Polyethylene Terephthalate CAS NO 25038-59-9

Product data	Thickness mm	Density Kg/m ³	Width mm	Length mm
Min	5	10	40	40
Max	100	100	2450	2500
Surface	According to specification			
Temperature	-30 +110 °C			
Lambda	0,038 W/mk			
Wash ability	Can be cleaned with water on the top surface. Needs to drip dry. CE Produkter AB takes no responsibility if chemicals or hard mechanical use is handled on AIRFELT – AIRFELT TK.			
Emissions	Approved according REIS Ref. 6F006139			
Humidity	Product is not effected by humidity			
Fire testing	Approved according EN 13501-1 (B S1 D0) SP Ref. P601926A			
Transportation	Not hazardous goods			

Environment & Recycling:

Any connection between AIRFELT - AIRFELT TK and any environmental damage has not been proven.

All waste from the production can be recycled by the manufacturer or be incinerated in a recycling facility. Local restrictions apply. AIRFELT - AIRFELT TK only emits carbon dioxide and water when incinerated.

Handling & Work environment:

In the case of cutting the material use an even blade to achieve a clean edge.
Protective clothing or face mask is not necessary.

Health aspects:

AIRFELT - AIRFELT TK has been used in the furniture-, bedding-, health care- and office environment industries since the 1960 with out any known difficulties.

AIRFELT - AIRFELT TK does not cause allergies, skin irritation or respiration problems. The material does not mould, is free from odour and does not emit gas or emission.