

DECLARATION OF PERFORMANCE N. CPR-NO1/0459

- 1) Unique identification code of the product-type: **ULTRALITE S2 FLEX QUICK**
- 2) Intended uses: **Improved, fast setting cementitious adhesive for internal and external tiling on floors and walls**
- 3) Manufacturer: **MAPEI AS – Vallsetvegen 6 – 2021 Sagstua – Norway - www.mapei.no**
- 4) Systems of AVCP: **System 3**
System 4 (for reaction to fire)
- 5) Harmonized standards: **EN 12004:2007+A1:2012**

Notified bodies: **SINTEF, N. 1071. carried out the assessment of the performance on the basis of testing on samples taken by the manufacturer.**

- 6) Performances declared:

Essential characteristics	Performances
Reaction to fire:	Class E
Bond strength:	expressed as: - initial tensile adhesion strength $\geq 1,0 \text{ N/mm}^2$ - early tensile adhesion strength $\geq 0,5 \text{ N/mm}^2$
Durability of bond strength against:	expressed as:
- climate/heat ageing action:	- tensile adhesion strength after heat ageing $\geq 1,0 \text{ N/mm}^2$
- water/humidity action:	- tensile adhesion strength after water immersion $\geq 1,0 \text{ N/mm}^2$
- freeze-thaw cycles:	- tensile adhesion strength after freeze-thaw cycles $\geq 1,0 \text{ N/mm}^2$
Release of dangerous substances:	NPD

- 7) Appropriate Technical Documentation: **included, as long as needed, in the technical dossier stored by the manufacturer. Reaction to fire class declared without the need for testing according to the Commission Decision 2010/81/EU.**
Organic material < 20% by weight **Maximum layer thickness 20 mm**

The performance of the product identified above is in conformity with the set of declared performances.

This declaration of performance is issued, in accordance with Regulation (EU) no. 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by: **Trond Hagerud – General Manager**
Sagstua, 16/03/2023



REACH information: the information referred to Article 31 or, as appropriate, to Article 33 of the REACH Regulation (EC) no. 1907/2006 and following amendments are indicated in the safety data sheet that MAPEI makes available on the website along with this current Declaration of Performance.

DoP in Pdf format are available in the Mapei website

Revision 0 notes:	First issue
--------------------------	--------------------

ULTRALITE S2 FLEX QUICK
CE MARKING
Annex to DoP N. CPR-NO1/0459



	 Valsetvegen 6 – 2021 Sagstua (Norway) www.mapei.no
<p style="text-align: center;">23 CPR-NO1/0459 EN 12004 ULTRALITE S2 FLEX QUICK <i>Improved, fast setting cementitious adhesive for internal and external tiling on floors and walls</i></p>	
Reaction to fire: Bond strength: Durability of bond strength against: <ul style="list-style-type: none"> - climate/heat ageing action: - water/humidity action: - freeze-thaw cycles: Release of dangerous substances:	Class E expressed as: <ul style="list-style-type: none"> - initial tensile adhesion strength $\geq 1,0 \text{ N/mm}^2$ - early tensile adhesion strength $\geq 0,5 \text{ N/mm}^2$ expressed as: <ul style="list-style-type: none"> - tensile adhesion strength after heat ageing $\geq 1,0 \text{ N/mm}^2$ - tensile adhesion strength after water immersion $\geq 1,0 \text{ N/mm}^2$ - tensile adhesion strength after freeze-thaw cycles $\geq 1,0 \text{ N/mm}^2$ NPD

Note:

MAPEI supplies the current annex along with the DoP to make the consultancy of the CE marking easier for the international clients. The enclosed CE marking can be slightly different compared to the one printed on the relevant packaging or documentation because of:

- NPD (No Performance Determined) values can be omitted by the CE marking
- graphic adaptations due to lack of space on the packaging or printing methods used,
- different language (the same packaging can be shared by several countries),
- the product is already in stock when the updating of the CE marking is implemented,
- printing mistakes.